



Figure similar

MLFB-Ordering data

6SL3210-5FB10-8UA0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Rated data

Input

Number of phases	1 AC
Line voltage	200 ... 240 V +10 % -15 %
Line frequency	45 ... 66 Hz

Output

Rated power	0.75 kW
Rated current (IN)	4.70 A
Max. output current	14.10 A

Inputs / outputs

Standard digital inputs

Number	10
--------	----

Digital outputs

Number	6
--------	---

Analog inputs

Number	2
--------	---

Analog outputs

Number	2
--------	---

Mechanical data

Degree of protection	IP20 / UL open type
Size	FSC
Net weight	1.95 kg
Width	80.0 mm
Height	170.0 mm
Depth	195.0 mm

Ambient conditions

Cooling	natural convection
---------	--------------------

Installation altitude	1000 m
-----------------------	--------

Ambient temperature

Operation	0 ... 45 °C
-----------	-------------

Storage	-40 ... 70 °C
---------	---------------

Relative humidity

Max. operation	90 %
----------------	------

Standards

Compliance with standards	CE, KC, cULus, EAC, C-Tick (RCM)
---------------------------	----------------------------------