



Figure similar

MLFB-Ordering data

6SL3210-5FB10-2UF2

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Rated data		Ambient conditions	
<b>Input</b>		<b>Cooling</b>	natural convection
Number of phases	1 AC	<b>Installation altitude</b>	1000 m
Line voltage	200 ... 240 V +10 % -15 %	<b>Ambient temperature</b>	
Line frequency	45 ... 66 Hz	<b>Operation</b>	0 ... 45 °C
<b>Output</b>		<b>Storage</b>	-40 ... 70 °C
Rated power	0.20 kW	<b>Relative humidity</b>	
Rated current (IN)	1.40 A	<b>Max. operation</b>	90 %
Max. output current	4.20 A		

Inputs / outputs		Standards	
<b>Standard digital inputs</b>		<b>Compliance with standards</b>	
Number	4	CE, KC, cULus, EAC, C-Tick (RCM)	
<b>Digital outputs</b>			
Number	2		
<b>Analog inputs</b>			
Number	2		

Mechanical data	
<b>Degree of protection</b>	IP20 / UL open type
<b>Frame size</b>	FSA
<b>Net weight</b>	1.10 kg
<b>Width</b>	45.0 mm
<b>Height</b>	170.0 mm
<b>Depth</b>	170.0 mm