OMRON Automatisation industrielle



E2E-X2R5D1-M1TGJ 0.3M

Détecteur de proximité, ind, laiton-nickel, m12, blindé, 2 mm, no, câble pig-tail 0.3 m, dc 2 fils

Spécifications

Size	M12
Mounting type	Flush
Sensing distance	2.5 mm
Overall length	47 mm
Thread length	32.9 mm
Material housing	Brass, nickel plated
Output type	2-wire
Operation mode	NO
Connection method	M12 pigtail Smartclick connector
Cable specifications	PVC (oil-resistant)
Cable length	0.3 m
IO-Link function	✖
Degree of protection (IP)	IP67/IP67G/IP69K

Produits liés



Connecteurs et câbles de connexion M12
Connecteurs et câbles de connexion industriels pour toutes les applications

Téléchargements


Bibliothèque CAO



E2E NEXT

Datasheet


EN PDF 39 Mo



E2E(Q) - Basic Models

Index

EN PDF 719 ko



E2E(Q) - Premium Models

Index

EN PDF 719 ko



EAC Mark removal

Avis d'interruption

EN PDF 221 ko



IO-Link Series

Brochure

FR PDF 4,09 Mo

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 13 November, 2023. Cliquez ici pour consulter les conditions d'utilisation.