OMRON Automatisation industrielle



E2E-X3D28-M1TGJ 0.3M

Détecteur de proximité, ind, laiton-nickel, m8, blindé, 3 mm, nc, câble pig-tail 0.3 m, dc 2 fils

Spécifications

Size	M8
Mounting type	Quasi-flush
Sensing distance	3 mm
Overall length	37.8 mm
Thread length	21 mm
Material housing	Brass, nickel plated
Output type	2-wire
Operation mode	NC
Connection method	M12 pigtail Smartclick connector
Cable specifications	PVC (oil-resistant)
Cable length	0.3 m
IO-Link function	✖
Degree of protection (IP)	IP67/IP67G/IP69K

Accessoires



Y92E-J8S12 Manchons de fixation e-jig pour M8 Prox

Produits liés




Connecteurs et câbles de connexion M12
Connecteurs et câbles de connexion industriels pour toutes les applications

Téléchargements


Bibliothèque CAO



E2E NEXT
Datasheet
EN PDF 39 Mo



E2E(Q) - Basic Models
Index
EN PDF 719 ko



E2E(Q) - Premium Models
Index
EN PDF 719 ko



EAC Mark removal
Avis d'interruption
EN PDF 221 ko



IO-Link Series
Brochure
FR PDF 4,09 Mo

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 13 November, 2023. Cliquez ici pour consulter les conditions d'utilisation.