OMRON Automatisation industrielle



E2E-X3D28-TR 2M

Détecteur de proximité, ind, laiton-nickel, m8, blindé, 3 mm, nc, câble robotique 2 m, dc 2 fils, sans polarité

Spécifications

Size	M8
Mounting type	Quasi-flush
Sensing distance	3 mm
Overall length	37.8 mm
Thread length	21 mm
Material housing	Brass, nickel plated
Output type	2-wire
Operation mode	NC
Connection method	Cable
Cable specifications	PVC (oil-resistant)
Cable length	2 m
IO-Link function	✖
Features	Flexible cable
Degree of protection (IP)	IP67/IP67G/IP69K

Accessoires



Y92E-J8S12 Manchons de fixation e-jig pour M8 Prox

Téléchargements


Bibliothèque CAO



E2E NEXT

Datasheet


EN PDF 39 Mo



E2E(Q) - Basic Models

Index

EN PDF 719 ko



E2E(Q) - Premium Models

Index

EN PDF 719 ko



EAC Mark removal

Avis d'interruption

EN PDF 221 ko



IO-Link Series

Brochure

FR PDF 4,09 Mo

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 13 November, 2023. Cliquez ici pour consulter les conditions d'utilisation.