OMRON Automatisation industrielle



E2E-X40MB3DL30-M1

Capteur de proximité, inductif, nickel-laiton, corps long, M30, non blindé, 40 mm, DC, 3 fils, PNP NO+NC, IO-Link COM2, connecteur M12

Spécifications

Size	M30
Mounting type	Non-flush
Sensing distance	40 mm
Overall length	80 mm
Thread length	50 mm
Material housing	Brass, nickel plated
Output type	PNP
Operation mode	NO + NC
Connection method	Connector M12
IO-Link function	✔
IO-Link baud rate	COM2 (38.4 kbps)
Degree of protection (IP)	IP67/IP69K

Produits liés



Connecteurs et câbles de connexion M12

Connecteurs et câbles de connexion industriels pour toutes les applications

Téléchargements


Bibliothèque CAO



E2E NEXT

Datasheet


EN PDF 39 Mo



E2E(Q) - Basic Models

Index

EN PDF 719 ko



E2E(Q) - Premium Models

Index

EN PDF 719 ko



E2E[Q]-XxBxxxx

Fichier IO-Link IODD

EN ZIP 1,35 Mo



EAC Mark removal

Avis d'interruption

EN PDF 221 ko



IO-Link Series

Brochure

FR PDF 4,09 Mo

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 13 November, 2023. Cliquez ici pour consulter les conditions d'utilisation.