OMRON Automatisation industrielle



E2E-X4B2L12-M1TJ 0.3M

Détecteur de proximité, inductif, laiton nickelé, corps long, M12, blindé, 4 mm, DC, 3 fils, PNP NC, M12 Smartclick Pig-tail 0.3 m

Spécifications

Size	M12
Mounting type	Quasi-flush
Sensing distance	4 mm
Overall length	69.1 mm
Thread length	55 mm
Material housing	Brass, nickel plated
Output type	PNP
Operation mode	NC
Connection method	M12 pigtail Smartclick connector
Cable specifications	PVC (oil-resistant)
Cable length	0.3 m
IO-Link function	✖
Degree of protection (IP)	IP67/IP67G/IP69K

Produits liés



Connecteurs et câbles de connexion M12
Connecteurs et câbles de connexion industriels pour toutes les applications

Téléchargements


Bibliothèque CAO



E2E NEXT

Datasheet


EN PDF 39 Mo



E2E(Q) - Basic Models

Index

EN PDF 719 ko



E2E(Q) - Premium Models

Index

EN PDF 719 ko



EAC Mark removal

Avis d'interruption

EN PDF 221 ko



IO-Link Series

Brochure

FR PDF 4,09 Mo

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 14 November, 2023. Cliquez ici pour consulter les conditions d'utilisation.