OMRON Automatisation industrielle



E2E-X5MB1T12 2M

Détecteur de proximité, inductif, nickel-laiton, corps court, M12, non blindé, 5 mm DC, 3 fils, PNP NO, IO-Link COM3, câble 2 m

Spécifications

Size	M12
Mounting type	Non-flush
Sensing distance	5 mm
Overall length	47.1 mm
Thread length	26 mm
Material housing	Brass, nickel plated
Output type	IO-Link, PNP
Operation mode	NO
Connection method	Cable
Cable specifications	PVC (oil-resistant)
Cable length	2 m
IO-Link function	✔
IO-Link baud rate	COM3 (230.4 kbps)
Degree of protection (IP)	IP67/IP67G/IP69K

Téléchargements


Bibliothèque CAO



E2E NEXT

Datasheet


EN PDF 39 Mo



E2E(Q) - Basic Models

Index


EN PDF 719 ko



E2E(Q) - Premium Models

Index

EN PDF 719 ko



E2E[Q]-XxBxxxx

Fichier IO-Link IODD

EN ZIP 1,35 Mo



EAC Mark removal

Avis d'interruption

EN PDF 221 ko



IO-Link Series

Brochure

FR PDF 4,09 Mo

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 17 November, 2023. Cliquez ici pour consulter les conditions d'utilisation.