



E2E-X6B1TL12-M1TJ 0.3M

Détecteur de proximité inductif, laiton nickelé, à corps long, M12, blindé, 6 mm, DC, 3 fils, PNP NO, IO-Link COM3, M12
Smartclick Pig-tail 0.3 m

Spécifications

Size	M12
Mounting type	Quasi-flush
Sensing distance	6 mm
Overall length	69.1 mm
Thread length	54 mm
Material housing	Brass, nickel plated
Output type	IO-Link, PNP
Operation mode	NO
Connection method	M12 pigtail Smartclick connector
Cable specifications	PVC (oil-resistant)
Cable length	0.3 m
IO-Link function	✓
IO-Link baud rate	COM3 (230.4 kbps)
Degree of protection (IP)	IP67/IP67G/IP69K

Produits liés



Connecteurs et câbles de connexion M12

Connecteurs et câbles de connexion industriels pour toutes les applications

Bibliothèque CAO



E2E NEXT Datasheet

EN PDF 39 Mo



E2E(Q) - Basic Models Index

EN PDF 719 ko



E2E(Q) - Premium Models Index

EN PDF 719 ko



E2E[Q]-XxBxxxx Fichier IO-Link IODD

EN ZIP 1,35 Mo



EAC Mark removal Avis d'interruption

EN PDF 221 ko



IO-Link Series Brochure

FR PDF 4,09 Mo

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 17 November, 2023. Cliquez ici pour consulter les [conditions d'utilisation](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU