



E2E-X6MD18-R 5M

Détecteur de proximité inductif inox m8, non-blindé, 6 mm, no, câble robotique 5 m, dc 2 fils

Spécifications

Size	M8
Mounting type	Non-flush
Sensing distance	6 mm
Overall length	37.8 mm
Thread length	20 mm
Material housing	Stainless steel
Output type	2-wire
Operation mode	NO
Connection method	Cable
Cable specifications	PVC (oil-resistant)
Cable length	5 m
IO-Link function	✗
Features	Flexible cable
Degree of protection (IP)	IP67/IP67G/IP69K

Bibliothèque CAO



E2E NEXT Datasheet

EN PDF 39 Mo



E2E(Q) - Basic Models Index

EN PDF 719 ko



E2E(Q) - Premium Models Index

EN PDF 719 ko



EAC Mark removal Avis d'interruption

EN PDF 221 ko



IO-Link Series Brochure

FR PDF 4,09 Mo

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 17 November, 2023. Cliquez ici pour consulter les [conditions d'utilisation](#).

OMRON

INDUSTRIAL AUTOMATION | [INDUSTRIAL.OMRON.EU](https://www.industrial.omron.eu)