



## E2E-X6MD28-T 5M

Détecteur de proximité, inductif, inox, m8, non-blindé, 6 mm, nc, câble 5 m, dc 2 fils, pas de polarité

# Spécifications


|                           |                     |
|---------------------------|---------------------|
| Size                      | M8                  |
| Mounting type             | Non-flush           |
| Sensing distance          | 6 mm                |
| Overall length            | 37.8 mm             |
| Thread length             | 20 mm               |
| Material housing          | Stainless steel     |
| Output type               | 2-wire              |
| Operation mode            | NC                  |
| Connection method         | Cable               |
| Cable specifications      | PVC (oil-resistant) |
| Cable length              | 5 m                 |
| IO-Link function          | ✗                   |
| Degree of protection (IP) | IP67/IP67G/IP69K    |

## Bibliothèque CAO



### E2E NEXT Datasheet

EN PDF 39 Mo



### E2E(Q) - Basic Models Index

EN PDF 719 ko



### E2E(Q) - Premium Models Index

EN PDF 719 ko



### EAC Mark removal Avis d'interruption

EN PDF 221 ko



### IO-Link Series Brochure

FR PDF 4,09 Mo

## CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 18 November, 2023. Cliquez ici pour consulter les [conditions d'utilisation](#).

**OMRON**

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU