



E2E-X8B1T18 10M

Détecteur de proximité, inductif, nickel-laiton, corps court, M18, blindé, 8 mm DC, 3 fils, PNP NO, IO-Link COM3, câble 10 m

Spécifications

Size	M18
Mounting type	Quasi-flush
Sensing distance	8 mm
Overall length	55.3 mm
Thread length	34 mm
Material housing	Brass, nickel plated
Output type	IO-Link, PNP
Operation mode	NO
Connection method	Cable
Cable specifications	PVC (oil-resistant)
Cable length	10 m
IO-Link function	✓
IO-Link baud rate	COM3 (230.4 kbps)
Degree of protection (IP)	IP67/IP67G/IP69K

Accessoires



Y92E-J18S30

Manchons de fixation e-jig pour M18 Prox

Bibliothèque CAO



E2E NEXT Datasheet

EN PDF 39 Mo



E2E(Q) - Basic Models Index

EN PDF 719 ko



E2E(Q) - Premium Models Index

EN PDF 719 ko



E2E[Q]-XxBxxxx Fichier IO-Link IODD

EN ZIP 1,35 Mo



EAC Mark removal Avis d'interruption

EN PDF 221 ko



IO-Link Series Brochure

FR PDF 4,09 Mo

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 18 November, 2023. Cliquez ici pour consulter les [conditions d'utilisation](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU