



E2E-X8MB1TL12 5M

Détecteur de proximité inductif, nickel-laiton, corps long m12, non blindé, 8 mm, dc, 3-fils, pnp no, io-link com3, 5 m précâblé

Spécifications


Size	M12
Mounting type	Non-flush
Sensing distance	8 mm
Overall length	69.1 mm
Thread length	48 mm
Material housing	Brass, nickel plated
Output type	IO-Link, PNP
Operation mode	NO
Connection method	Cable
Cable specifications	PVC (oil-resistant)
Cable length	5 m
IO-Link function	✓
IO-Link baud rate	COM3 (230.4 kbps)
Degree of protection (IP)	IP67/IP67G/IP69K

Bibliothèque CAO



E2E NEXT Datasheet

EN PDF 39 Mo



E2E(Q) - Basic Models Index

EN PDF 719 ko



E2E(Q) - Premium Models Index

EN PDF 719 ko



E2E[Q]-XxBxxxx Fichier IO-Link IODD

EN ZIP 1,35 Mo



EAC Mark removal Avis d'interruption

EN PDF 221 ko



IO-Link Series Brochure

FR PDF 4,09 Mo

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 19 November, 2023. Cliquez ici pour consulter les [conditions d'utilisation](#).