



## E2E-X8MB3DL12 2M

Détecteur de proximité, inductif, nickel-laiton, corps long, M12, non blindé, 8 mm DC, 3 fils, PNP NO + NC, IO-Link COM2,  
câble 2 m

# Spécifications


|                           |                      |
|---------------------------|----------------------|
| Size                      | M12                  |
| Mounting type             | Non-flush            |
| Sensing distance          | 8 mm                 |
| Overall length            | 69.1 mm              |
| Thread length             | 48 mm                |
| Material housing          | Brass, nickel plated |
| Output type               | IO-Link, PNP         |
| Operation mode            | NO + NC              |
| Connection method         | Cable                |
| Cable specifications      | PVC (oil-resistant)  |
| Cable length              | 2 m                  |
| IO-Link function          | ✓                    |
| IO-Link baud rate         | COM2 (38.4 kbps)     |
| Degree of protection (IP) | IP67/IP67G/IP69K     |

## Bibliothèque CAO



### E2E NEXT Datasheet

EN PDF 39 Mo



### E2E(Q) - Basic Models Index

EN PDF 719 ko



### E2E(Q) - Premium Models Index

EN PDF 719 ko



### E2E[Q]-XxBxxxx Fichier IO-Link IODD

EN ZIP 1,35 Mo



### EAC Mark removal Avis d'interruption

EN PDF 221 ko



### IO-Link Series Brochure

FR PDF 4,09 Mo

## CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 19 November, 2023. Cliquez ici pour consulter les [conditions d'utilisation](#).

**OMRON**

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU