OMRON Automatisation industrielle



E2EQ-X12B3D18-M1

Proximity sensor, inductive, Fluororesin coating (base material: brass), M18, shielded, 12 mm, DC, 4-wire, PNP NO+NC, IO-Link COM2, M12 connector

Spécifications

Features	Fluoroplastic coating
Size	M18
Mounting type	Flush
Sensing distance	12 mm
Overall length	53 mm
Material housing	Brass, PTFE coated
Output type	IO-Link, PNP
Operation mode	NO + NC
Connection method	Connector M12
Cable specifications	-
IO-Link baud rate	COM2 (38.4 kbps)
Degree of protection (IP)	IP67/IP69K

Produits liés



Connecteurs et câbles de connexion M12

Connecteurs et câbles de connexion industriels pour toutes les applications

Téléchargements


Bibliothèque CAO



E2E NEXT

Datasheet


EN PDF 39 Mo



E2E(Q) - Basic Models

Index


EN PDF 719 ko



E2E(Q) - Premium Models

Index

EN PDF 719 ko



E2E[Q]-XxBxxxx

Fichier IO-Link IODD

EN ZIP 1,35 Mo



EAC Mark removal

Avis d'interruption

EN PDF 221 ko

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 19 November, 2023. Cliquez ici pour consulter les conditions d'utilisation.