OMRON Automatisation industrielle



# E2FM-X2C1 2M

M12, blindé, Sn: 2 mm, L: 53(33) mm, 10-30 Vc.c., NPN, NO, connecteur M12

# Spécifications

| | |
|---|---|
| **Size** | M12 |
| **Mounting type** | Flush |
| **Sensing distance** | 2 mm |
| **Output type** | NPN |
| **Operation mode** | NO |
| **Connection method** | Cable |
| **Material housing** | Stainless steel |
| **Cable specifications** | PVC |
| **Cable length** | 2 m |
| **Overall length** | 53 mm |
| **Thread length** | 33 mm |
| **Features** | Metal sensing face |
| **Polarity** | ✔ |
| **Degree of protection (IP)** | IP67 |

# Téléchargements

**Bibliothèque CAO**



**E2FM Inductive Proximity Sensor in full metal housing**

**Datasheet**

FR PDF 1,02 Mo



**EAC Mark removal**

**Avis d'interruption**

EN PDF 221 ko



**Proximity Sensors**

**Brochure**

FR PDF 4,3 Mo

**CONDITIONS D'UTILISATION**

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 21 November, 2023. Cliquez ici pour consulter les conditions d'utilisation.

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU