OMRON Automatisation industrielle



E32-C91N 2M

Fibre optique réflexion directe, tête de détection M6 hex 90°, flexible, 2m

Spécifications

Sensing method	Diffuse reflective
Shape	Threaded
Size	M6
Application	Object detection
Features	90° cable exit, Flexible fiber, Hexagonal back, Small spot with lens
Temperature range	-40-70 °C
Sensing distance	1170 mm
Cable length	2 m
Bending radius	4 mm
Free cut	✔
Material core	Plastic
Degree of protection (IP)	IP67
Sensing surface orientation	Right-angle
Material sheath	Polyethylene

Accessoires



E39-F18 ACCESS POUR CELL PHOTO

Produits liés



E3NX-CA
Détection de repères colorés haute performance



E3NX-CA
Détection de repères colorés haute performance



E3NX-FA
Amplificateur à fibre numérique hautes performances



E3NX-MA
Amplificateurs à fibre intelligents



E3X-NA
Amplificateur à fibre numérique avec réglage par potentiomètre



E3X-HD
Amplificateur numérique à fibre facile à utiliser



E3X-ZV et E3X-MZV
Amplificateur à fibre intelligent

Téléchargements

Bibliothèque CAO



E3NX-CA Color Fiber Amplifier Unit

Datasheet

EN PDF 1,05 Mo



EAC Mark removal

Avis d'interruption

EN PDF 221 ko



Fiber Optic Sensors

Catalogue groupe

EN PDF 7,54 Mo



Fiber Sensor Selection

Guide de sélection

EN PDF 15,3 Mo

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 12 February, 2024. Cliquez ici pour consulter les conditions d'utilisation.