

E32-D15ZR 2M

Fiber optic sensor head, diffuse, square, flat-view, R1 flexible fiber, 2 m cable

Specifications

Sensing method	Diffuse reflective
Shape	Square
Product Width (unpacked)	3 mm
Product Depth (unpacked)	10 mm
Product Height (unpacked)	15 mm
Application	Object detection
Features	Flexible fiber
Temperature range	-40-70 °C
Sensing distance	300 mm
Cable length	2 m
Free cut	✓
Material core	Plastic
Degree of protection (IP)	IP67
Sensing surface orientation	Flat-view
Material sheath	PVC

Related products



E3NX-CA

High-performance color mark sensor



E3NX-CA

High-performance color mark sensor



E3NX-MA

Smart Fiber Amplifier Units



E3NX-FA

High-performance digital fiber amplifier



E3X-NA

Digital fiber amplifier with potentiometer adjustment



E3X-HD

Easy-teach digital fiber amplifier



E3X-ZV and E3X-MZV

Smart Fiber Amplifier

Downloads

CAD Library




E32-ETS14R-1 Datasheet

EN PDF 84.8 KB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Fiber Sensor Selection Selection Guide

EN PDF 15.3 MB

