



E32-L25L 2M

Réflexion directe, 16 x 18 x 4 mm, rayon de courbure 10 mm, focalisée, E3X-DA-SE-S: $7,2 \pm 1,8$ mm

Spécifications

Sensing method	Limited reflective
Shape	Square
Product Width (unpacked)	18 mm
Product Depth (unpacked)	4 mm
Product Height (unpacked)	16 mm
Application	Object detection
Temperature range	-40-70 °C
Sensing distance	7 mm
Cable length	2 m
Bending radius	10 mm
Free cut	✓
Material core	Plastic
Degree of protection (IP)	IP50
Sensing surface orientation	Top-view
Material sheath	Polyethylene

Produits liés



E3NX-CA

Détection de repères colorés haute performance



E3NX-CA

Détection de repères colorés haute performance



E3NX-FA

Amplificateur à fibre numérique hautes performances



E3NX-MA

Amplificateurs à fibre intelligents



E3X-NA

Amplificateur à fibre numérique avec réglage par potentiomètre



E3X-HD

Amplificateur numérique à fibre facile à utiliser



E3X-ZV et E3X-MZV

Amplificateur à fibre intelligent

Téléchargements

Bibliothèque CAO



EAC Mark removal Avis d'interruption

EN PDF 221 ko



Fiber Sensor Selection Guide de sélection

EN PDF 15,3 Mo

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 12 February, 2024. Cliquez ici pour consulter les [conditions d'utilisation](#).

OMRON

INDUSTRIAL AUTOMATION | [INDUSTRIAL.OMRON.EU](https://industrial.omron.eu)