PILZ
THE SPIRIT OF SAFETY

PSEN rs1.0-175 570301



Rope pull switch incl. E-STOP pushbutton, metal housing, 2xNC+2xNO contacts, 175 N max. spring force.

Technical details

General data	
Approval:	CE, BG, cCSAus
Technical data	
Relay outputs	
Utilisation cat. AC15/DC13sta.:	EN 60947-5-1
Voltage AC15 safety cont.:	240
Max. current AC15 safety cont.:	3
Voltage DC13 safety cont.:	250
Environmental data	
Ambient temperature:	-30 - 80 °C
Protection type, housing:	IP67
Mechanical data	
Housing material lower section:	Aluminium-Druckguss
Housing material upper part:	Aluminium-Druckguss
Material actuator:	Zn-Druckguss
Connection terminal:	Schraubklemme
Height dimension:	88
Width dimension:	282
Depth dimension:	90.09999999999999
Net weight:	933

Gross weight:	1052
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6b, 6c
REACh compliance:	contains min. 1 SVHC-substance
REACh included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
WEEE classifikation (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27270607
ETIM Version:	ETIM-7.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC002033

Optional accessories



380706 PDP67 cable M12-5sm, 10m



380707 PDP67 cable M12-5sm, 20m



380705 PDP67 cable M12-5sm, 3m

	570314	PSEN rs rope d3/d4 50m
	380708	PDP67 cable M12-5sm, 30m
	570315	PSEN rs rope d3/d4 100m
	570312	PSEN rs pulley 75
	570313	PSEN rs pulley flex
	570310	PSEN rs spring 175
	773600	PDP67 F 8DI ION
	570311	PSEN rs spring 300
	570793	PSEN cable 200m-8x0.25mm²