# DATASHEET



## AZ3350-B1

- Particularly suitable for sliding doors

## Data

### Ordering data

| | |
|---|---|
| Product type description | AZ3350-B1 |
| Article number (order number) | 101214015 |
| EAN (European Article Number) | 4030661446363 |
| eCl@ss number, version 12.0 | 27-27-26-06 |
| eCl@ss number, version 11.0 | 27-27-26-06 |
| eCl@ss number, version 9.0 | 27-27-26-06 |
| ETIM number, version 7.0 | EC001487 |
| ETIM number, version 6.0 | EC001487 |

### General data

| | |
|---|---|
| Coding level according to EN ISO 14119 | Low |
| Material of the actuator | Stainless steel (V2A) |
| Gross weight | 48 g |

### Mechanical data

| | |
|---|---|
| Actuating radius, minimum | 400 mm |

| | |
|---|---|
| Actuator | straight<br>rigid |

### Note

| | |
|---|---|
| Note (General) | minimum actuating radius on rotating guard systems via the narrow edge of the actuator 700 mm<br>minimum actuating radius on hinged guards in line with the plane of the actuator 400 mm<br>The axis of the hinge must be 28 mm above and in a parallel plane to the top surface of the safety switch. |


## Pictures

### Product picture (catalogue individual photo)



ID: kaz33f16
| 392.3 kB | .jpg | 312.208 x 518.583 mm - 885 x 1470 px - 72 dpi
| 46.1 kB | .png | 74.083 x 122.767 mm - 210 x 348 px - 72 dpi
| 30.1 kB | .jpg | 74.436 x 123.472 mm - 211 x 350 px - 72 dpi

### Dimensional drawing actuator




ID: 1shgvb01
| 30.2 kB | .cdr |
| 4.2 kB | .png | 74.083 x 51.506 mm - 210 x 146 px - 72 dpi
| 95.9 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695 px - 72 dpi